

Gemini² Dual Containment® Value-Pak Tank Packages

Package Comparison			
Feature	Silver Package	Gold Package	Platinum Package
Gemini ² Dual Containment® Tank	✓	✓	✓
CAD Drawings	✓	✓	✓
PVC Fittings	✓	✓	✓
Float Gauge	✓	✗	✗
Pump Pedestal	✓	✓	✓
1" Fill Inlet with Quick Connect Coupler	✓	✓	✓
Gemini Pump Suction Tube	✓	✓	✓
Double Wall Bulkhead Bottom Drain Fitting	✗	✓	✗
Double Wall Welded Bottom Drain Fitting	✗	✗	✓
Level Indicator	✗	✓	✓
Restraint	✗	✓	✓
Leak Detection	✗	✗	✓
Level Sensor	✗	✗	✓
3P Document Protector	✓	✓	✓
Shipping Prep	✓	✓	✓

Feature Details	
Gemini² Dual Containment® Tank	The square Gemini ² Dual Containment® Tanks have 22% more capacity than cylindrical tanks of the same size and meet or exceed secondary containment regulations set under EPA 49CFR. These tanks are designed with a pump mounting surface, female threaded connections, and twist lid inspection port. The integral mouse door, molded directly into most Gemini models, is a recessed mouse door that allows for the inexpensive installation of an optional dual wall bulkhead fitting for flooded suction and bottom fill applications.
CAD Drawings	Provided to ensure the tank meets the application needs.
PVC Fittings	The plastic fittings are durable and won't corrode or rust over time.
Float Gauge	The manual float-type level gauges are made of stainless steel and polyethylene and give instant level readings with levels listed in an easy-to-read format in 1/8, 1/4, 3/8, 1/2, 5/8, 3/4 & full. (PVDF float gauges are available for an additional cost.)
Pump Pedestal	Elevates pumps, sold separately, for easy suction tubing connection.
1" Fill Inlet with Quick Connect Coupler	Includes a male cam adapter and dust cap with lanyard.
Gemini Pump Suction Tube	Suction tube with a foot valve makes connection easy.
Double Wall Bulkhead Bottom Drain Fitting	Pre-installed 1" double wall bulkhead bottom drain fitting.
Double Wall Welded Bottom Drain Fitting	Pre-installed 1" double wall welded bottom drain fitting.
Level Indicator	Mini inverse level indication with a 2" wide calibration board.
Restraint	Fiber ring restraint system (non-code).
Leak Detection	Interstitial leak detection sensor. (An alarm box option is available for an additional cost.)
Level Sensor	Submersible level sensor and display with 4-20mA signal output and 24 VDC power.
3P Document Protector	Attaches important documents, like safety data sheets, to the side of the tank.
Shipping Prep	Each tank is palletized and wrapped to protect it from elements during transit.