



FEATURES

LINER

Gray GRAPHENE Liner,
Fine Gauge

COATING

Black HCT MicroFoam Nitrile
Palm Coating

BENEFITS:

- ANSI Cut Level A3
- EN388 Cut Level 4
- Excellent Abrasion Resistance
- Excellent Heat Resistance
- Excellent Cut Resistance
- Anti-Bacterial
- High Tensile Strength
- UV Resistance
- Anti-Static

CATEGORY:

Graphene

APPLICATIONS:

- Aerospace
- Appliance Manufacturing
- Automotive Manufacturing
- Construction
- Glass Work
- Logistics
- Packaging
- Metal Fabrication
- Plastic Injection Molding

Armor Guys reference number : 00-300

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



SPECIFICATIONS

LINER MATERIALS	Gray Graphene Liner
COATING MATERIALS	Black HCT MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XS -XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	72	72	72	72	72	72
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4442C	EN Level 4 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F
IMPACT	X	F	P			

