m	GROU	~	
	anou	Ապ	¥

**TECHNICAL DATA** 

## 58RTO P27/2WHBNA BLACK v4

Codes:AA012008

Customer code:

All rights reserved. Any disclosure or reproduction to a third person is submitted to an authorization.

DEFINITION	4 lug cap for vacuum sealing on threaded ring with the following designation:					GME 20-04 (GPI 2020)	
PROFILED PANEL	RTO Regular Twist Off / RTO						
SIZES	Please refer to d	rawing ET	58H10RTO	at the botto	m of the page.		
METAL	<u>Category:</u> tin s All the metal cha		ckness: 0,155 mm mply to the Europe	-	2.8/2.8 g/m <sup>2</sup>		
COMPOUND (P27)	Food contact compound PVC ESBO suitable for non-fatty products and pasteurisation heat treatments up to 100°C. Nominal compound thickness 0.8 mm +/- 0.20 mm						
INTERIOR PROTECTION (2WHBN)	For fairly corrosive and corrosive products: 1 operation of base coat BPA NI + Top coat varnish BPA NI						
PROTECTION AND EXTERIOR DECORATION	Please refer to drawing MNA-01829T58999						
DECLARATION OF CONFORMITY	Please refer to declarations of conformity						
PACKAGING	Average weight of a cap: 7,3 g Gross average weight of a carton: 12,3 kg Number of caps/carton: 1575 (in plastic bags)						
(weights are given with ±		artons / pallet	Number of ca		Gross average weight	Pallet size	
10%)		40	6300	0	492		
STORAGE CONDITIONS AND DLUO	Please refer to Caps user guide for the Massilly group		regarding storage	regarding storage			
USE CONDITIONS	Please refer to	Caps user g	uide for the Massilly	r group	regarding caps and the	ir relevant use.	
DRAWING ET58H10RTO	10.10 maxi 8.20 mini		Outillage 42.33			056.30 mini 053.12 mini 060.30 maxi	

Printing Date: 02/08/2024

