

Fluid System Kits Service & Repair

Service and Repair Kits include various configurations of our most popular fittings in 1/4", 3/8" and 1/2" OD sizes within the Polypropylene Range. Fittings come in a sturdy and compartmentalized case for ease of storage and transportation.

Working pressures and temperatures

Water Max. 150 psi at 70 °F (Max. 10 bar at 20 °C)
 Max. 60 psi at 140 °F (Max. 4 bar at 60 °C)
 Min. 33 °F/1 °C

NOT suitable for compressed air applications.



NSF 51
NSF 61

Appliance Service & Repair Kit



Service and repair kits include the following:

Part Number

KIT-ISRKA

KIT INCLUDES

Part Number	Description	Qty
1/4SCV-US	1/4" Check Valve	2
3/8SCV-US	3/8" Check Valve	2
ASVPP5LF-US	1/2" x 3/8" x 1/4" Angle Stop Valve	1
ASVPP6LF-US	1/2" x 3/8" x 3/8" Angle Stop Valve	1
CI530808W	1/4" Stackable Tee	2
NC2099P	5/16" x 1/4" Reducing Union Connector	5
NC2723	3/8" OD Female Swivel Elbow	2
PP0308W-US	1/4" Union Elbow	5
PPM0308W	5/16" Union Elbow	5
PP0312W-US	3/8" Union Elbow	5
PP0408W-US	1/4" Union Connector	5
PPM0408W	5/16" Union Connector	5
PP0412W-US	3/8" Union Connector	5
PP0808W-US	1/4" Plug	5
PPM0808W	5/16" Plug	5
PP0812W	3/8" Plug	5
PP201208W	3/8" x 1/4" Reducing Union Connector	5
PP211008W	5/16" x 1/4" Reducing Elbow	5
PP211208W	3/8" x 1/4" Reducing Elbow	5
PP3208U7W-US	1/4" Faucet Connector UNS Thread	5
PPSV040808W	1/4" Straight Shut-Off Valve	1
PPSV041212W	3/8" Straight Shut-Off Valve	1
PPSV451223W	3/8" x 3/8" NPTF Female Shut-Off Valve	1
PSEI6012U9-US	3/8" Female Connector UNEF Thread	2
TSNIP-US	Tube Cutter	1